

	Down-link	RX Frequency	Up-Link
Low BEACON	10.489.550	739.550	DON'T TRANSMIT
	10.489.555	739.555	
CW Only	10.489.555	739.555	2400.055
	10489.560	739.560	2400.060
	10489.570	739.570	2400.070
	10489.580	739.580	2400.080
	10489.590	739.590	2400.090
	10489.600	739.600	2400.100
Narrow band digital mode (500Hz Max.BW)	10489.600	739.600	2400.100
	10489.610	739.610	2400.110
	10489.620	739.620	2400.120
Digital mode (2700Hz Max.BW)	10489.620	739.620	2400.120
	10489.630	739.630	2400.130
	10489.640	739.640	2400.140
Mixed mode (2700Hz Max.BW)	10489.640	739.640	2400.140
	10489.650	739.650	2400.150
	10489.660	739.660	2400.160
	10489.670	739.670	2400.170
	10489.680	739.680	2400.180
	10489.690	739.690	2400.190
SSB	10489.690	739.690	2400.190
	10489.700	739.700	2400.200
	10489.710	739.710	2400.210
	10489.720	739.720	2400.220
	10489.730	739.730	2400.230
	10489.740	739.740	2400.240
	10489.750	739.750	2400.250
	10489.760	739.760	2400.260
	10489.770	739.770	2400.270
	10489.780	739.780	2400.280
	10489.790	739.790	2400.290
	10489.795	739.795	2400.295
Up BEACON	10489.795	739.795	DON'T TRANSMIT
	10489.800	739.800	